

FREEZER COMPACT F420L C DR G U

Product series: Compact

Item number: 163422030

The HOSHIZAKI COMPACT F420L C DR G U is a FREEZER on castors with a net usable volume of 265 Ltr.

The COMPACT series offers a rare combination: These cabinets are food-safe, space-saving, and come with excellent energy ratings for their class. With a footprint of only 59.5 x 66.7 cm, these small space storage cabinets are easy to fit in, especially when space is limited. These specifications make the series such a popular choice for those operators who do not require heavy-duty Gastronorm equipment.



Food Safety

Thanks to the Hoshizaki air distribution system, temperatures are correct and uniform throughout the entire cold room, ensuring perfectly food-safe temperatures at all times

Low-Running Energy Costs

The Energy Efficiency Class of the COMPACT F420L C DR G U is C. The COMPACT series offers a range of extremely energy-efficient refrigeration units for small spaces.

Comfortable Work Environment

Contributes to a healthier work environment with low noise levels 39.7 dB(A), when the compressor is running. Low heat emission due to short compressor running times.

Hygiene & Ergonomic Design

The COMPACT series features several design extras, implemented to simplify daily cleaning routines. One of the features for optimized operator safety is the full-height integrated handles.

The COMPACT F420L C DR G U comes with:

Refrigerant: The FREEZER uses HC refrigerant R600a

Air circulation system

Right-hand hinged door

Integrated full-height door handle

Internal LED light

Reversible door

Door lock for extra security

White shelves

Automatic defrost with re-evaporation of defrost water

SPECIFICATIONS

Product title	FREEZER	Energy consumption (kWh/Year)	1,086
Temperature Range	-25/-5°C	Energy efficiency class standard	ISO 22041-2019
Volume, Gross (ltr.)	343	Energy efficiency class	C
Net Usable Volume (ltr.)	265	Energy Efficiency Index EEI	39.06
Exterior	White Finish	Sound Level – dB(A)	39.7
Interior	White Finish	Climate Class	4 (max. ambient temp. of 30 °C with 55% RH)
Dimensions W x D x H (mm)	595 x 645 x 1901	Legs / Castors	H = 125 mm (C2)
Weight, Packed (kg)	88	Refrigerant (kg)	0.047
Insulation (mm)	52 (polyurethane)	CO2 equivalent (kg)	0.141
Refrigerant	R600a	GN or Tray Size (mm)	Shelf 483.8 x 433 mm
GWP	3	Maximum number of shelves	26
Ref. Capacity at -25°C (Watt)	217	Number of shelves	5
Power Supply	230V, 50 Hz	Equipped with	Right hand hinged reversible door with lock, 5 white shelves, bottom shelf 484.7 (W) x 300 (D) mm. Exterior: White. Interior: PS lining in white
Connection Load (Watt)	140	Door Type	Insulated Door