

REFRIGERATOR COMPACT K420R C DR G U

Product series: Compact

Item number: 151422030

The HOSHIZAKI COMPACT K420R C DR G U is a REFRIGERATOR on castors with a net usable volume of 265 Ltr.

The COMPACT series offers a rare combination: These cabinets are food-safe, space-saving, and come with excellent energy ratings for their class. With a footprint of only 59.5 x 66.7 cm, these small space storage cabinets are easy to fit in, especially when space is limited. These specifications make the series such a popular choice for those operators who do not require heavy-duty Gastronorm equipment.



Food Safety

Thanks to the Hoshizaki air distribution system, temperatures are correct and uniform throughout the entire cold room, ensuring perfectly food-safe temperatures at all times

Low-Running Energy Costs

The Energy Efficiency Class of the COMPACT K420R C DR G U is B. The COMPACT series offers a range of extremely energy-efficient refrigeration units for small spaces.

Comfortable Work Environment

Contributes to a healthier work environment with low noise levels 39.8 dB(A), when the compressor is running. Low heat emission due to short compressor running times.

Hygiene & Ergonomic Design

The COMPACT series features several design extras, implemented to simplify daily cleaning routines. One of the features for optimized operator safety is the full-height integrated handles.

The COMPACT K420R C DR G U comes with:

Refrigerant: The REFRIGERATOR uses HC refrigerant R600a

Air circulation system

Right-hand hinged door

Integrated full-height door handle

Internal LED light

Reversible door

Door lock for extra security

White shelves

Automatic defrost with re-evaporation of defrost water

SPECIFICATIONS

| | | | |
|--------------------------------------|-------------------|---|--|
| Product title | REFRIGERATOR | Energy consumption (kWh/Year) | 310 |
| Temperature Range | +1/+12°C | Energy efficiency class standard | ISO 22041-2019 |
| Volume, Gross (ltr.) | 343 | Energy efficiency class | B |
| Net Usable Volume (ltr.) | 265 | Energy Efficiency Index EEI | 29.62 |
| Exterior | Stainless | Sound Level – dB(A) | 39.8 |
| Interior | White Finish | Climate Class | 4 (max. ambient temp. of 30 °C with 55% RH) |
| Dimensions W x D x H (mm) | 595 x 645 x 1901 | Legs / Castors | H = 125 mm (C2) |
| Weight, Packed (kg) | 87 | Refrigerant (kg) | 0.048 |
| Insulation (mm) | 52 (polyurethane) | CO2 equivalent (kg) | 0.144 |
| Refrigerant | R600a | GN or Tray Size (mm) | Shelf 483.8 x 433 mm |
| GWP | 3 | Maximum number of shelves | 26 |
| Ref. capacity at -10°C (Watt) | 122 | Number of shelves | 5 |
| Power Supply | 230V, 50 Hz | Equipped with | Right hand hinged reversible door with lock, 5 white shelves, bottom shelf 484.7 (W) x 300 (D) mm. Exterior: Stainless. Interior: PS lining in white |
| Connection Load (Watt) | 120 | Door Type | Insulated Door |