

GLASS DOOR REFRIGERATOR COMPACT KG420L C DR G U

Product series: Compact Item number: 164422030

The HOSHIZAKI COMPACT KG420L C DR G U is a GLASS DOOR REFRIGERATOR on castors with a net usable volume of $265\,\mathrm{Ltr.}$

The COMPACT series offers a rare combination: These cabinets are food-safe, space-saving, and come with excellent energy ratings for their class. With a footprint of only 59.5 x 66.7 cm, these small space storage cabinets are easy to fit in, especially when space is limited. These specifications make the series such a popular choice for those operators who do not require heavy-duty Gastronorm equipment.



Thanks to the Hoshizaki air distribution system, temperatures are correct and uniform throughout the entire cold room, ensuring perfectly food-safe temperatures at all times

Low-Running Energy Costs

The Energy Efficiency Class of the COMPACT KG420L C DR G U is D. The COMPACT series offers a range of extremely energy-efficient refrigeration units for small spaces.

Comfortable Work Environment

Contributes to a healthier work environment with low noise levels 39.8 dB(A), when the compressor is running. Low heat emission due to short compressor running times.

Hygiene & Ergonomic Design

The COMPACT series features several design extras, implemented to simplify daily cleaning routines. One of the features for optimized operator safety is the full-height integrated handles.

The COMPACT KG420L C DR G U comes with:

Refrigerant: The GLASS DOOR REFRIGERATOR uses HC refrigerant R600a

Air circulation system
Right-hand hinged door

Integrated full-height door handle

Internal LED light Reversible door

Door lock for extra security

White shelves

Automatic defrost with re-evaporation of defrost water

SPECIFICATIONS

Product title	GLASS DOOR REFRIGERATOR	Energy consumption (kWh/Year)	670
Temperature Range	+1/+12°C	Energy efficiency class standard	ISO 22041-2019
Volume, Gross (Itr.)	343	Energy efficiency class	D
Net Usable Volume (ltr.)	265	Energy Efficiency Index EEI	64.1
Exterior	White Finish	Sound Level – dB(A)	39.8
Interior	White Finish	Climate Class	4 (max. ambient temp. of 30 °C with 55%
Dimensions W x D x H (mm)	595 x 667 x 1901		RH)
Weight, Packed (kg)	99	Legs / Castors	H = 125 mm (C2)
Inquistion (mm)	F2 (polygrathona)	Refrigerant (kg)	0.048
Insulation (mm)	52 (polyurethane)	CO2 equivalent (kg)	0.144
Refrigerant	R600a	— GN or Tray Size (mm)	Shelf 483.8 x 433 mm
GWP	3	— GN of Tray Size (IIIII)	Shell 463.6 X 433 mm
Ref. capacity at -10°C (Watt)	122	Maximum number of shelves	26
	2201/ 50 11-	 Number of shelves 	5
Power Supply	230V, 50 Hz	Equipped with	Right hand hinged reversible glass door with
Connection Load (Watt)	130	_	lock, 5 white shelves, bottom shelf 484.7 (W) x 300 (D) mm, LED lighting. Exterior: White. Interior: PS lining in white
		Door Type	Glass door