## **SIEMENS**

## iQ500, Gas hob, 75 cm, Stainless steel EC7A5RB90





HZ211310 Simmer cap HZ233540 Wok ring HZ241110 Small pot support HZ298105 Simmer plate The gas hob with stepFlame Technology for precise flame control in nine steps.

- ✓ stepFlame Technology Precise flame control with nine different settings.
- ✓ Dual Wok Burner 5 kW Go from simmer to stir-fry on one burner.
- ✓ High-quality materials and workmanship continuous cast-iron pan supports.
- ✓ Biomethane ready Power your gas hob with renewable biomethane gas.
- ✓ The extremely convenient sword knob makes it easy to control and monitor the power level selected.

Product name/family:	gas hob w
integrated controls	
Built-in / Free-standing:	Built-in
Source of energy:	
Number of cooking zones:	
Type of control setting devices:	
Min. required niche size for installation (HxW	
480-492 mm	XD)43 X 300-302 X
Width of the appliance:	750 mm
Dimensions:	
Dimensions of the packed product (HxWxD):	
Weight:	
Gross weight:	
Residual heat indicator:	
Location of control panel:	
Basic surface material:	
Color of surface:	Stainless steel
Length electrical supply cord:	100.0 cm
EAN code:	4242003676134
Gas connection rating:	12500 W
Fuse protection:	
Nominal power:	
Frequency:	



## **SIEMENS**

# iQ500, Gas hob, 75 cm, Stainless steel EC7A5RB90

#### Design

- Stainless steel surface
- · Cast iron pan supports

#### Usage convenience

- Step Flame technology 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

#### Burners and power

- 5 burner gas hob including:
- Including 1 dual control wok burner: use an extra wide power range, separately controlling two flame rings.
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: wok burner up to 5 KW (depending on gas type)
- Right rear: High-speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

#### Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

### Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- $\bullet$  Dimensions of the product (HxWxD mm): 53 x 750 x 520
- $\bullet$  Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 12.5 KW

## iQ500, Gas hob, 75 cm, Stainless steel EC7A5RB90

