


iQ300, Gas hob, 60 cm, Stainless steel EG6B5PB90



HZ241110 Small pot support

The gas hob with front-mounted controls.

- ✓ High-quality materials and workmanship – continuous cast-iron pan supports.
- ✓ Biomethane ready – Power your gas hob with renewable biomethane gas.
- ✓ The sword knob combines highest ease of use with modern design.
- ✓ The uniquely beautiful stainless-steel surface design.

Product name/family: gas hob w integrated controls
 Built-in / Free-standing: Built-in
 Source of energy: Gas
 Number of cooking zones: 4
 Type of control setting devices: sword knobs
 Min. required niche size for installation (HxWxD):45 x 560-562 x 480-492 mm
 Width of the appliance: 582 mm
 Dimensions: 53 x 582 x 520 mm
 Dimensions of the packed product (HxWxD): ... 141 x 615 x 578 mm
 Weight: 9.6 kg
 Gross weight: 10.5 kg
 Residual heat indicator: without
 Location of control panel: Front
 Basic surface material: Stainless steel
 Color of surface: Stainless steel
 Length electrical supply cord: 100.0 cm
 EAN code:4242003836408
 Gas connection rating: 7500 W
 Fuse protection:3 A
 Nominal power:220-240 V
 Frequency:50; 60 Hz



iQ300, Gas hob, 60 cm, Stainless steel EG6B5PB90

Design

- Stainless steel surface
- Cast iron pan supports

Usage convenience

- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner gas hob including:
 - Left front: Standard burner up to 1.75 KW (depending on gas type)
 - Left rear: Standard burner up to 1.75 KW (depending on gas type)
 - Right rear: High-speed burner up to 3 KW (depending on gas type)
 - Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 582 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.5 KW

iQ300, Gas hob, 60 cm, Stainless steel
EG6B5PB90

