iQ500, Gas hob, 60 cm, Tempered glass, Black EP6A6HB20





Optional accessories

HZ211310	Simmer cap
HZ298105	Simmer plate
HZ298108	Wok ring
HZ298114	Small pot support

The gas hob with stepFlame Technology for precise flame control in nine steps.

- ✓ stepFlame Technology Precise flame control with nine different settings.
- ✓ This wok burner with up to 3.5 kW of power (depending on gas type) is ideal for a wide variety of foods, even in large quantities.
- ✓ High-quality materials and workmanship individual cast-iron pan supports.
- ✓ Biomethane ready Power your gas hob with renewable biomethane gas.
- ✓ The extremely convenient sword knob makes it easy to control and monitor the power level selected.

Features

)):45 x 560-562 x
590 mm
58 x 590 x 520 mm
141 x 651 x 578 mm
14.6 kg
15.5 kg
without
Front
Tempered glass
Black
Black
100.0 cm
4242003742389
8000 W
A
220-240 V
60; 50 Hz





iQ500, Gas hob, 60 cm, Tempered glass, Black EP6A6HB20

Features

Design

- Tempered Glass surface, black
- frameless design: install the hob either flush or slightly raised on the worktop
- Cast iron w rubber feet single

Usage convenience

- Step Flame technology 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner gas hob including:
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: WOK burner up to 3.5 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- \bullet Dimensions of the product (HxWxD mm): 58 x 590 x 520
- \bullet Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 8 KW

2 /



iQ500, Gas hob, 60 cm, Tempered glass, Black EP6A6HB20

