

FLAKER, MODULAR FM-480AWKE-R452-SB

Product series: FM

Item number: F082-C222

This Hoshizaki FM-480AWKE-R452-SB is a modular flake ice maker producing up to 420 kg of high-quality flake ice per 24 hours.

Hoshizaki FM ice makers generate quality granular ice, such as Flake ice. The light texture of granular ice has a quick cooling effect, creating an environment of uniform temperatures, without causing unpleasant freezer-burn. This is why Hoshizaki Flake ice is highly popular and considered the ideal material to prepare and layer hygienic and attractive food displays.

For flake ice, the extruding head is equipped with wide channels and multi-blade cutters.

The FM-480AWKE-R452-SB uses refrigerant R452A.

Material

The exterior and the auger are made of stainless steel. The closed water circuit provides maximum protection against any type of contamination during ice production. All Hoshizaki machines are easy to use, clean, and maintain.

Unique Technology

The inner workings of Flakers are designed to prevent unpleasant calcification and bacterial contamination. For example, the use of carbon graphite bushings instead of conventional ball bearings allows the machine to work entirely without grease.

Smart Design

Like all Hoshizaki Ice makers, the FM-480AWKE-R452-SB is designed to last and comes with smart design extras, such as the intuitive control display for preventive maintenance.

Perfect Fit

Need to amp up your production capacity? The variable setups with modular bins and bases allow the user to mix and match depending on individual requirements and conditions. The dimensions of the FM-480AWKE-R452-SB are mm.

Plug&Play

The smart plug-and-play design guarantees an easy and quick set-up.



SPECIFICATIONS

Product title	Flaker, Modular	Net Weight (kg)	95
Production Capacity (kg/24h) approx. (AT 10°C, WT 10°C)	420	Gross Weight, Packed (kg)	102
Power Supply	1/220 - 240V/50Hz	Corresponding bin(s)	B140SA, B210SA, B340SA
Electric Consumption (kW)	1,385	Icemaking Water Consumption (m³/24h) approx. (AT 10°C, WT 10°C)	0,42
Ice type	Flake	Icemaking Water Consumption (m³/24h) approx. (AT 21°C, WT 15°C)	0,38
Refrigerant	R452A	Icemaking Water Consumption (m³/24h) approx. (AT 32°C, WT 21°C)	0,34
CO2 equivalent (kg)	791,8	Condenser Water Consumption flow (m³/24h) approx. (AT 10°C, WT 10°C)	1,207
Cooling System	Water Cooled	Condenser Water Consumption (m³/24h) approx. (AT 21°C, WT 15°C)	1,622
Product configuration	Modular	Condenser Water Consumption (m³/24h) approx. (AT 32°C, WT 21°C)	2,41