

IM-45WNE-HC

Cuber, Self Contained

Production Capacity (kg/24h) approx. (AT 10°C, WT 10°C): 45

Storage bin capacity (kg) approx.: 18



ICE TYPE: Large cubes, Standard





ACCESSORIES INCLUDED

Scoop, legs, installation kit

OPTIONAL ACCESSORIES

4HC-H water filtration, external drain pump

CORRESPONDING WATER FILTERS

4HC-H Single Water Filter, 4HC Replacement Cartridge

PRODUCT SERIES: IM ITEM NUMBER: M064-D002 COUNTRY OF ORIGIN: UK

Hoshizaki IM-45WNE-HC is a self-contained water cooled ice maker producing up to $45~{\rm kg}$ of cube ice per $24~{\rm hours}$.

Hoshizaki recommends that the water-cooled condenser should be connected to a closed circuit recirculating type cooling systemutilizing a tower, water chiller or similar. Water make up should be via a ball valve/break tank arrangement. Whilst connecting a water-cooled condenser to a mains water (potable) supply will not affect the performance of the machine, it will most certainly cause high water use and waste of a valuable resource that is not recommended. It is likely that the connection of such units to the mains water supply may be a contravention of local water authority by-laws.

Ice cube dimensions and weight - disclaimer: The drawing is for illustration purposes only. Cube size and weight may be differ due to local installation conditions.

- Ice making system with an automatic rinse cycle
- Each ice cycle is made with fresh water
- Closed Cell System helps produce compact, hard and geometrically perfect
 ice.
- Closed water circuit for contamination protection
- Electronic controller
- System comes with a magnetic water pump that has no direct coupling, which prevents any leakage
- Removable door gasket

WARRANTY PERIOD 2 Years on Parts & Labour

EXTERIOR
Stainless steel AISI 430, Galvanized steel
(Rear)


Refrigerant: R290 / Refrigerant (kg): 0.09 / CO2 equivalent (kg): 0.27

OPERATING CONDITIONS

Ambient Temp.: 1-40°C, Water Supply Temp.: 5-35°C, Water Supply Pressure: 0.07-0.8MPa (0.7-8bar), Voltage Range: Rated Voltage ±6%



IM-45WNE-HC



TECHNICAL SPECIFICATIONS

ſ	Cooling System	Production Capacity	ion Capacity Production Capacity Production Capacity		Power Supply	Electrical Circuit	Electric	Water Consumption	Heat Rejection (AT					
1		(kg/24h) approx.	(kg/24h) approx.	(kg/24h) approx.		Breaker Protection	Consumption (kW)	(m3/24h) approx.	32°C, WT 21°C)					
		(AT 10°C, WT 10°C)	(AT 21°C WT 15°C)	(AT 32°C WT 21°C)		(A)		(AT 10°C WT 10°C)	(kW)					
	Water Cooled	45	40	37	1/220 - 240V/50Hz	5	0.24	0.25	0.5					

SHIPPING SPECIFICATIONS

Dimensions W x D x H (mm), legs excluded	Dimensions of Legs (mm)	Net Weight (kg)	Dimensions, Packed, W x D x H (mm)	Gross Weight, Packed (kg)	Volume Packed (m3)
503 x 456 x 840	for legs add 90-125 mm	45	635 x 520 x 1007	53	0.33

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

Please observe: This type of icemaker is on special order only. Please take longer lead times into consideration.



Hoshizaki Belgium Hoshizaki Danmark Hoshizaki Deutschland Hoshizaki France Hoshizaki Iberia Hoshizaki Italia Hoshizaki Middle East info@hoshizaki.be
info@hoshizaki.dk
vertrieb@hoshizaki.de
info@hoshizaki.fr
info@hoshizaki.es
commerciale@hoshizaki.it
sales.ex@hoshizaki-europe.com

Hoshizaki Netherlands Hoshizaki Norge Hoshizaki Sverige Hoshizaki UK Export countries Other countries info@hoshizaki.nl salg@hoshizaki.no orderSE@hoshizaki.dk uksales@hoshizaki.uk sales.ex@hoshizaki-europe.com sales.ex@hoshizaki-europe.com

www.hoshizaki-europe.com