

**iQ100, Canopy cooker hood, 53 cm, Anthracite
LB53NAA30B**



Optional accessories

LZ10INA00	Standard odor filter (replacement)
LZ10INT00	Standard recirculation kit

The powerful canopy cooker hood is concealed in a unit above the hob.

✓ LED lights: for optimal visibility and ambience while cooking.

Features

Technical Data

Typology: Built-in/Built-under
 Length electrical supply cord: 150.0 cm
 Min. required niche size for installation (HxWxD): 208mm x 493.0mm x 257mm mm
 Minimum distance above an electric hob: 550 mm
 Minimum distance above a gas hob: 650 mm
 Weight: 4.5 kg
 Control panel: mechanical
 Number of speed settings: 3
 Maximum output air extraction: 302 m³/h
 Maximum output recirculating air: 300 m³/h
 Maximum Air flow: 302 m³/h
 Number of lights: 2
 Noise level: 62 dB(A) re 1 pW
 Diameter of air outlet: 120 mm
 Grease filter material: Washable aluminium
 EAN code: 4242003831717
 Connection Rating: 121 W
 Fuse protection: 5 A
 Nominal power: 220-240 V
 Frequency: 50 Hz
 Plug type: GB plug
 Installation type: Built-in



iQ100, Canopy cooker hood, 53 cm, Anthracite LB53NAA30B

Features

Key performance features:

- Energy Efficiency Class: D (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 302 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB*

Features

- Push button control for extractor speeds and light
- 3 x power levels
- 2 x 3W LED
- Colour Temperature: 2700 K
- 1 x metal grease filter cassette
- Installation: integrated

Design

- Canopy hood
- Mechanical

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Extraction rate according to EN 61591: max. 302 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 62 dB(A) re 1 pW (48 dB(A) re 20 µPa sound pressure)
- Power rating: 121 W
- Light Intensity: 78 lux
- Electrical cable length 1.5 m
- Diameter pipe Ø 120 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 208-208 x 534 x 300 mm
- Dimensions recirculating, chimney (HxWxD): 208-208 x 534 x 300mm
- Built-in dimensions (HxWxD): 208 x 493 x 257 mm
- Blower Efficiency Class: E*
- Lighting Efficiency Class: D*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 67.7 kWh/year*

Optional accessories

- Recirculating kit LZ10INA00

* In accordance with the EU-Regulation No 65/2014

iQ100, Canopy cooker hood, 53 cm, Anthracite
LB53NAA30B

Dimensioned drawings

