

**iQ100, Integrated cooker hood,  
60 cm, Silver  
LE66MAC00B**



This fold-out integrated hood with a high extraction rate for powerful performance is hidden in the upper cabinet unit.

✓ LED lights: for optimal visibility and ambience while cooking.

Features

Technical Data

Typology: ..... Built-in/Built-under  
 Length electrical supply cord: ..... 150.0 cm  
 Minimum distance above an electric hob: ..... 500 mm  
 Minimum distance above a gas hob: ..... 650 mm  
 Weight: ..... 10.7 kg  
 Control panel: ..... mechanical  
 Number of speed settings: ..... 3  
 Maximum output air extraction: ..... 625 m³/h  
 Maximum output recirculating air: ..... 416 m³/h  
 Maximum Air flow: ..... 625 m³/h  
 Number of lights: ..... 2  
 Noise level: ..... 70 dB(A) re 1 pW  
 Diameter of air outlet: ..... 150 / 120 mm  
 Grease filter material: ..... Washable aluminium  
 EAN code: ..... 4242003806500  
 Connection Rating: ..... 256 W  
 Fuse protection: ..... 10 A  
 Nominal power: ..... 220-240 V  
 Frequency: ..... 50; 60 Hz  
 Plug type: ..... GB plug  
 Installation type: ..... Wall-mounted



4 242003 806500

Optional accessories

LZ10IMA00 Standard odor filter

**iQ100, Integrated cooker hood,  
60 cm, Silver  
LE66MAC00B**

Features

**Key performance features:**

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 625 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB\*

**Features**

- Push button control for extractor speeds and light
- 3 x power levels
- 2 x 3W LED
- 2 x metal grease filter cassettes

**Design**

- Integrated hood
- Installation: Between Cupboards
- Mechanical

**Performance/technical information**

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 68.4 kWh/year\*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating, chimney (HxWxD): 402-402 x 599 x 271 mm

**Optional accessories**

- Recirculating kit LZ10IMA00

\* In accordance with the EU-Regulation No 65/2014

iQ100, Integrated cooker hood,  
60 cm, Silver  
LE66MAC00B

Dimensioned drawings

