



HOSHIZAKI

2-SECTION REFRIGERATED COUNTER SCR-130DG-LR-RRC-C1 U

Product series: Snowflake GII

Item number: 879000861

The Snowflake GII series is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staffs all around the world.

The technology behind the performance boost of Snowflake GII is the tropicalised cooling system enduring up to +40°C. Additionally, the cooling agent of the new generation of Snowflake is the eco-friendly refrigerant R290, a natural gas (HC) that enhances the performance and cuts down energy consumption significantly.

Both interior and exterior are built of anti-corrosion stainless steel, which is among the best choices for hygienic and food safe cooking environments.

The Snowflake GII SCR-130DG-LR-RRC-C1 U is a 2-section refrigerated counter with a net internal volume of 171 Ltr.

As a product that is designed and built to last, this refrigerated counter combines an innovative design concept, premium materials and clever extras:

- Minimum cool air lost: double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Both interior and exterior are built of stainless steel which is among the best choices for hygienic and food safe cooking environments
- Anti-tilt mechanism: extra-long drawers with u-shaped, telescopic rails
- Multiple door-drawer combinations possible
- Removable gaskets make sure you can clean the device thoroughly
- This and other thoughtful extras, such as the cleaning-free condenser, are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

The refrigerant used in all Snowflake GII HC models is R290.

This agent is a natural gas which enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential.



SPECIFICATIONS

Product title	2-Section Refrigerated Counter	Connection Load (Watt)	160
Temperature Range	-2/+8°C	Energy consumption (kWh/Year)	905
Volume, Gross (ltr.)	300	Energy efficiency class	C
Net Usable Volume (ltr.)	171	Energy Efficiency Index EEI	40.63
Exterior	Stainless	Climate Class	5 (max. ambient 40°C w/ 40% RH)
Interior	Stainless	Legs / Castors	H = 150mm (C1)
Dimensions W x D x H (mm)	1314 x 700 x 856 (with castors)	Refrigerant (kg)	0.055
Weight, Packed (kg)	112	CO2 equivalent (kg)	0.165
Insulation (mm)	50 (cyclopentane)	GN or Tray Size (mm)	1/1 GN
Refrigerant	R290	Number of shelves	4
GWP	3	Equipped with	Stainless steel worktop, 2 door sections each with 2 grey shelves
Ref. capacity at -10°C (Watt)	316	Door Type	Insulated Door
Power Supply	230V, 50 Hz		